

Declaration of Performance

DoP №: G520-2026

- Unique identification code of the product-type: Gyproc® + Product-type
- Product-types: GN 13, GNE 13, GN 13 NW, GN 13 Klima, GE 13, 4PRO, GKBI 13, GS 6, GSE 6, GTS 9, GTS 13, GEK 13, GEKE 13, GR 13, GR 13 Klima, GRI 13, GRIE 13, GL 15, GF 15, GFE 15, GF 15 WN and GF 18
Batch identification consist of date and time of production – YYYY-MM-DD HH:MM
- Intended use: General building construction works
- Manufacturer:
 - Saint-Gobain Finland Oy, PL 44, FI-02401 Kirkkonummi
 - Gyproc AB, Box 153, SE-74624 Bålsta
 - Gyproc AS, Habornveien 59, NO-1630 Gamle Fredrikstad
 - Saint-Gobain Construction Products Polska Sp. z o.o., Szarbków 73 • 28-400 Pińczów • Polska
- Authorized representative: Saint-Gobain Finland Oy
- System of assessment and verification of constancy of performance: System 3
- Determination of the product-type, on the basis of type testing in accordance with EN 520:2004 under System 3, has been performed by:
 - SP Swedish National Testing and Research Institute, NB 0402, performed type testing of reaction to Fire and issued the classification reports no. P504782A, P504782C, P6022554A
 - VTT Expert Service Oy, NB 0809 and The Danish Technological Institute, NB 1235, have performed type testing of Shear Strength and issued test reports VTT-S-04726-13 and 1316346-09
- European Technical Assessment (ETA): N/A
- Declared performance:

Essential characteristics

Product	CE Performance Type:	Reaction to fire:	Shear strength:	Water vapour resistance factor:	Lämmönjohtavuus	Impact resistance	Airborne sound insulation	Acoustic absorption	Environmental impact:			
GS6, GSE 6	D-6,5	A2-s1, d0	NPD	10	0,25 W/m•K	NPD	See Gyproc Handbook	See Gyproc Handbook	Hazardous substances: None Indoor emissions: None Dangerous waste: None			
GTS 9	EH2-9,5	A2-s1, d0	290 N	10	0,25 W/m•K	NPD						
GTS 13	EH2-12,5	A2-s1, d0	500 N	10	0,25 W/m•K	NPD						
GN 13, GNE 13, GN 13 WN, GN 13 Klima, 4Pro	A-12,5	A2-s1, d0	370 N	10	0,25 W/m•K	NPD						
GE 13	A-12,5	A2-s1, d0	350 N	10	0,15 W/m•K	NPD						
GEK 13, GEKE 13	DIR-12,5	A2-s1, d0	500 N	10	0,25 W/m•K	NPD						
GR 13, GR 13 WN, GR 13 Klima	DIR-12,5	A2-s1, d0	500 N	10	0,25 W/m•K	NPD						
GRI 13, GRIE 13	DIRH2-12,5	A2-s1, d0	520 N	10	0,25 W/m•K	NPD						
GKBI 13	AH2-12,5	A2-s1, d0	NPD	10	0,25 W/m•K	NPD						
GL 15	DIR-15,5	B-s1, d0	520 N	10	0,25 W/m•K	NPD						
GFE 15	DFI-15,4	A2-s1, d0	440 N	10	0,25 W/m•K	NPD						
GF 15, GF 15 WN	DF-15,4	A2-s1, d0	NPD	10	0,25 W/m•K	NPD						
GF 18	DF-18,0	A2-s1, d0	NPD	10	0,25 W/m•K	NPD						
Harmonised technical specification	EN 520:2004 +A1:2009	EN 13501-1:2002 EN 520:2004 +A1:2009 CWFT	EN 520:2004 +A1:2009	EN 12524:2000 EN ISO 12572	EN 12524:2000	EN 520:2004 +A1:2009						

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Kimmo Anttila, Head of Offer Management, Nordic & Baltic Countries
 (name and function)

Kirkkonummi, 24.4.2026
 (Place and date of issue)



(signature)